

METHOD AND SYSTEM FOR ROUTE PLANNING

FIELD OF INVENTION

The present invention relates generally to computing systems and, more particularly, to a method and system for enabling route planning.

5 CO-PENDING APPLICATIONS

Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of the present invention simultaneously with the present invention:

10 ~~NPA011US, NPA031US, NPA040US, NPA046US, NPA053US, NPA059US,
NPA064US, NPB006US, NPS004US, NPS008US, NPS013US, NPS024US,
NPPC1, UP01US, UP02US, UP03US, UP04US, UP05US~~

The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be

15 ~~replaced by the corresponding USSN when available.~~

Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of the present invention on 15 September 2000:

20 ~~NPA024US, NPA025US, NPA047US, NPA049US~~

The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be replaced by the corresponding USSN when available.

25 Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of the present invention on 30 June 2000:

30 ~~NPA014US, NPA015US, NPA022US, NPA026US, NPA038US, NPA041US,
NPA050US, NPA051US, NPA052US, NPA063US, NPA065US, NPA067US,
NPA068US, NPA069US, NPA071US, NPA072US, NPB003US, NPB004US,
NPB005US, NPP019US, PEC04US, PEC05US, PEC06US, PEC07US~~

The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be replaced by the corresponding USSN when available.

Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of the present invention on 23 May 2000:

*Sub
Part*

5 NPA001US, NPA002US, NPA004US, NPA005US, NPA006US, NPA007US,
NPA008US, NPA009US, NPA010US, NPA012US, NPA016US, NPA017US,
NPA018US, NPA019US, NPA020US, NPA021US, NPA030US, NPA035US,
NPA048US, NPA075US, NPB001US, NPB002US, NPK002US, NPK003US,
NPK004US, NPK005US, NPM001US, NPM002US, NPM003US, NPM004US,
NPN001US, NPP001US, NPP003US, NPP005US, NPP006US, NPP007US,
10 NPP008US, NPP016US, NPP017US, NPP018US, NPS001US, NPS003US,
NPS020US, NPT001US, NPT002US, NPT003US, NPT004US, NPX001US,
NPX003US, NPX008US, NPX011US, NPX014US, NPX016US, IJ52US,
IJM52US, MJ10US, MJ11US, MJ12US, MJ13US, MJ14US,
MJ15US, MJ34US, MJ47US, MJ58US, MJ62US, MJ63US,
15 PAK04US, PAK05US, PAK06US, PAK07US, PAK08US, PEC01US,
PEC02US, PEC03US

The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be
20 ~~replaced by the corresponding USSN when available.~~

BACKGROUND

A variety of route planning systems and devices are known. Some are provided on general-purpose computer systems such as personal computers or on the World Wide Web, while others are provided as part of dedicated devices such as automobile navigation systems. The traveler, who is typically a driver, specifies a starting point, a destination and optionally a number of intermediate way-points, and the route planning system automatically plans a suitable route.

A typical automobile navigation system uses GPS to track the location of the car. It may provide automatic route planning, or it may only allow the driver to enter a route planned by other means. In any case the navigation system typically assists the driver in following the route by displaying local mapping data keyed to the car's current location and issuing directions to the driver to follow the route. It may also utilize synthesized spoken instructions.

Route planning systems suffer from a number of problems. Route planning is often not integrated with an automobile navigation system where it is needed, requiring manual and laborious entry of way-points. Where it is integrated, the limited size and resolution of navigation system screens make the entry of locations awkward.

SUMMARY OF INVENTION

It is an objective of the present invention to provide a new method and system for enabling route planning.

The present invention provides, in a first aspect, a method of enabling a user to plan a route using a computer system, the method including the steps of:

printing a map of a geographic area, the map including coded data indicative of an identity of the map and of a plurality of reference points of the map;

receiving, in the computer system, indicating data from a sensing device operated by the user, the indicating data regarding the identity of the map and a position of the sensing device relative to the map, the sensing device, when placed in an operative position relative to the map, sensing the indicating data using at least some of the coded data;

identifying, in the computer system and from the indicating data, at least one geographic location; and

planning the route, in the computer system, using the at least one geographic location as at least one of: the route starting point, a route way-point, and the route
5 destination.

Preferably, the method includes the further step of printing a map covering at least part of the geographic area covered by the route.

The present invention provides, in a second aspect, a system for enabling a user to plan a route, the system including:

10 a map of a geographic area, the map including coded data indicative of an identity of the map and of a plurality of reference points of the map;

a printer for printing the map, including the coded data, on demand; and

a computer system for receiving indicating data from a sensing device operated by the user, the indicating data regarding the identity of the map and a position of the
15 sensing device relative to the map, the sensing device, when placed in an operative position relative to the map, sensing the indicating data using at least some of the coded data;

wherein the computer system is configured to identify, from the indicating data, at least one geographic location, and to plan the route using the at least one geographic
20 location as at least one of: the route starting point, an route way-point, and the route destination.

Accordingly, the present invention provides a method and system which utilizes one or more forms capable of interacting with a computer system. Whilst the novel method and system of the present invention may be used in conjunction with a
25 single computer system, in a particularly preferred form it is designed to operate over a computer network, such as the Internet.

BRIEF DESCRIPTION OF DRAWINGS

Preferred and other embodiments of the invention will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

- 5 Figure 1 is a schematic of a the relationship between a sample printed netpage and its online page description;

Figure 2 is a schematic view of a interaction between a netpage pen, a netpage printer, a netpage page server, and a netpage application server;

- 10 Figure 3 is a schematic view of a high-level structure of a printed netpage and its online page description;

Figure 4a is a plan view showing a structure of a netpage tag;

Figure 4b is a plan view showing a relationship between a set of the tags shown in Figure 4a and a field of view of a netpage sensing device in the form of a netpage pen;

Figure 5a is a plan view showing an alternative structure of a netpage tag;

- 15 Figure 5b is a plan view showing a relationship between a set of the tags shown in Figure 5a and a field of view of a netpage sensing device in the form of a netpage pen;

Figure 5c is a plan view showing an arrangement of nine of the tags shown in Figure 5a where targets are shared between adjacent tags;

- 20 Figure 5d is a plan view showing the interleaving and rotation of the symbols of the four codewords of the tag shown in Figure 5a;

Figure 6 is a schematic view of a set of user interface flow document icons;

Figure 7 is a schematic view of a set of user interface page layout element icons;

Figure 8 illustrates the route planning user class diagram;

Figure 9 illustrates the map class diagram;

- 25 Figure 10 illustrates the street class diagram;

Figure 11 illustrates the route planning class diagram;

Figure 12 illustrates the route feature class diagram;

Figure 13 illustrates the route plan class diagram;

Figure 14 illustrates the route planning user interface flow;

Figure 15 illustrates the trip origin page;

Figure 16 illustrates the trip destination page;

5 Figure 17 illustrates the preferences page;

Figure 18 illustrates the route plan page; and

Figure 19 illustrates the printer's high-speed serial interface between the navigation system and the netpage printer.

Figure 13 illustrates the route plan class diagram;

DETAILED DESCRIPTION OF PREFERRED AND OTHER EMBODIMENTS

Note: Memjet™ is a trademark of Silverbrook Research Pty Ltd, Australia.

Sub
A5

~~In the preferred embodiment, the invention is configured to work with the netpage networked computer system, a summary of which is given below and a detailed description of which is given in our earlier applications, including in particular applications USSN 09/_____ (docket no. NPT002US), USSN 09/_____ (docket no. NPS001US), USSN 09/_____ (docket no. NPP003US), USSN 09/_____ (docket no. NPA002US) and USSN 09/_____ (docket no. IJ52US). It will be appreciated that not every implementation will necessarily embody all or even most of the specific details and extensions described in these applications in relation to the basic system. However, the system is described in its most complete form to assist in understanding the context in which the preferred embodiments and aspects of the present invention operate.~~

In brief summary, the preferred form of the netpage system employs a computer interface in the form of a mapped surface, that is, a physical surface which contains references to a map of the surface maintained in a computer system. The map references can be queried by an appropriate sensing device. Depending upon the specific implementation, the map references may be encoded visibly or invisibly, and defined in such a way that a local query on the mapped surface yields an unambiguous map reference both within the map and among different maps. The computer system can contain information about features on the mapped surface, and such information can be retrieved based on map references supplied by a sensing device used with the mapped surface. The information thus retrieved can take the form of actions which are initiated by the computer system on behalf of the operator in response to the operator's interaction with the surface features.

In its preferred form, the netpage system relies on the production of, and human interaction with, netpages. These are pages of text, graphics and images printed on ordinary paper or other media, but which work like interactive web pages. Information is encoded on each page using ink which is substantially invisible to the unaided human eye. The ink, however, and thereby the coded data, can be sensed by an optically imaging pen and transmitted to the netpage system.

In the preferred form, active buttons and hyperlinks on each page can be clicked with the pen to request information from the network or to signal preferences to a network server. In one embodiment, text written by hand on a netpage is automatically recognized and converted to computer text in the netpage system, allowing forms to be filled in. In other embodiments, signatures recorded on a netpage are automatically verified, allowing e-commerce transactions to be securely authorized.

As illustrated in Figure 1, a printed netpage 1 can represent a interactive form which can be filled in by the user both physically, on the printed page, and "electronically", via communication between the pen and the netpage system. The example shows a "Request" form containing name and address fields and a submit button. The netpage consists of graphic data 2 printed using visible ink, and coded data 3 printed as a collection of tags 4 using invisible ink. The corresponding page description 5, stored on the netpage network, describes the individual elements of the netpage. In particular it describes the type and spatial extent (zone) of each interactive element (i.e. text field or button in the example), to allow the netpage system to correctly interpret input via the netpage. The submit button 6, for example, has a zone 7 which corresponds to the spatial extent of the corresponding graphic 8.

Sub ab
~~As illustrated in Figure 2, the netpage pen 101, a preferred form of which is described in our earlier application USSN 09/_____ (docket no. NPS001US), works in conjunction with a netpage printer 601, an Internet-connected printing appliance for home, office or mobile use. The pen is wireless and communicates securely with the netpage printer via a short-range radio link 9.~~

The netpage printer 601, preferred forms of which are described in our earlier application USSN 09/_____ (docket no. NPP003US) and our co-filed application USSN 09/_____ (docket no. NPS024US), is able to deliver, periodically or on demand, personalized newspapers, magazines, catalogs, brochures and other publications, all printed at high quality as interactive netpages. Unlike a personal computer, the netpage printer is an appliance which can be, for example, wall-mounted adjacent to an area where the morning news is first consumed, such as in a user's kitchen, near a breakfast table, or near the household's point of departure for the day. It ~~also comes in tabletop, desktop, portable and miniature versions.~~

Netpages printed at their point of consumption combine the ease-of-use of paper with the timeliness and interactivity of an interactive medium.

As shown in Figure 2, the netpage pen 101 interacts with the coded data on a printed netpage 1 and communicates, via a short-range radio link 9, the interaction to a netpage printer. The printer 601 sends the interaction to the relevant netpage page server 10 for interpretation. In appropriate circumstances, the page server sends a corresponding message to application computer software running on a netpage application server 13. The application server may in turn send a response which is printed on the originating printer.

Sal 017 ~~The netpage system is made considerably more convenient in the preferred embodiment by being used in conjunction with high-speed microelectromechanical system (MEMS) based inkjet (Memjet™) printers, for example as described in our earlier application USSN 09/_____ (docket no. IJ52US). In the preferred form of this technology, relatively high-speed and high-quality printing is made more affordable to consumers. In its preferred form, a netpage publication has the physical characteristics of a traditional newsmagazine, such as a set of letter-size glossy pages printed in full color on both sides, bound together for easy navigation and comfortable handling.~~

The netpage printer exploits the growing availability of broadband Internet access. The netpage printer can also operate with slower connections, but with longer delivery times and lower image quality. The netpage system can also be enabled using existing consumer inkjet and laser printers, although the system will operate more slowly and will therefore be less acceptable from a consumer's point of view. In other embodiments, the netpage system is hosted on a private intranet. In still other embodiments, the netpage system is hosted on a single computer or computer-enabled device, such as a printer.

Netpage publication servers 14 on the netpage network are configured to deliver print-quality publications to netpage printers. Periodical publications are delivered automatically to subscribing netpage printers via pointcasting and multicasting Internet protocols. Personalized publications are filtered and formatted according to individual user profiles.

A netpage printer can be configured to support any number of pens, and a pen

can work with any number of netpage printers. In the preferred implementation, each netpage pen has a unique identifier. A household may have a collection of colored netpage pens, one assigned to each member of the family. This allows each user to maintain a distinct profile with respect to a netpage publication server or application server.

A netpage pen can also be registered with a netpage registration server 11 and linked to one or more payment card accounts. This allows e-commerce payments to be securely authorized using the netpage pen. The netpage registration server compares the signature captured by the netpage pen with a previously registered signature, allowing it to authenticate the user's identity to an e-commerce server. Other biometrics can also be used to verify identity. A version of the netpage pen includes fingerprint scanning, verified in a similar way by the netpage registration server.

Although a netpage printer may deliver periodicals such as the morning newspaper without user intervention, it can be configured never to deliver unsolicited junk mail. In its preferred form, it only delivers periodicals from subscribed or otherwise authorized sources. In this respect, the netpage printer is unlike a fax machine or e-mail account which is visible to any junk mailer who knows the telephone number or e-mail address.

Each object model in the system is described using a Unified Modeling Language (UML) class diagram. A class diagram consists of a set of object classes connected by relationships, and two kinds of relationships are of interest here: associations and generalizations. An association represents some kind of relationship between objects, i.e. between instances of classes. A generalization relates actual classes, and can be understood in the following way: if a class is thought of as the set of all objects of that class, and class A is a generalization of class B, then B is simply a subset of A. Each class is drawn as a rectangle labelled with the name of the class. It contains a list of the attributes of the class, separated from the name by a horizontal line, and a list of the operations of the class, separated from the attribute list by a horizontal line. In the class diagrams which follow, however, operations are never modelled. An association is drawn as a line joining two classes, optionally labelled at either end with the multiplicity of the association. The default multiplicity is one. An asterisk (*) indicates a multiplicity

of “many”, i.e. zero or more. Each association is optionally labelled with its name, and is also optionally labelled at either end with the role of the corresponding class. An open diamond indicates an aggregation association (“is-part-of”), and is drawn at the aggregator end of the association line. A generalization relationship (“is-a”) is drawn as a solid line joining two classes, with an arrow (in the form of an open triangle) at the generalization end. When a class diagram is broken up into multiple diagrams, any class which is duplicated is shown with a dashed outline in all but the main diagram which defines it. It is shown with attributes only where it is defined.

Netpages are the foundation on which a netpage network is built. They provide a paper-based user interface to published information and interactive services. A netpage consists of a printed page (or other surface region) invisibly tagged with references to an online description of the page. The online page description is maintained persistently by a netpage page server. The page description describes the visible layout and content of the page, including text, graphics and images. It also describes the input elements on the page, including buttons, hyperlinks, and input fields. A netpage allows markings made with a netpage pen on its surface to be simultaneously captured and processed by the netpage system.

Multiple netpages can share the same page description. However, to allow input through otherwise identical pages to be distinguished, each netpage is assigned a unique page identifier. This page ID has sufficient precision to distinguish between a very large number of netpages.

Each reference to the page description is encoded in a printed tag. The tag identifies the unique page on which it appears, and thereby indirectly identifies the page description. The tag also identifies its own position on the page. Characteristics of the tags are described in more detail below.

Tags are printed in infrared-absorptive ink on any substrate which is infrared-reflective, such as ordinary paper. Near-infrared wavelengths are invisible to the human eye but are easily sensed by a solid-state image sensor with an appropriate filter.

A tag is sensed by an area image sensor in the netpage pen, and the tag data is transmitted to the netpage system via the nearest netpage printer. The pen is wireless and communicates with the netpage printer via a short-range radio link. Tags are sufficiently

small and densely arranged that the pen can reliably image at least one tag even on a single click on the page. It is important that the pen recognize the page ID and position on every interaction with the page, since the interaction is stateless. Tags are error-correctably encoded to make them partially tolerant to surface damage.

- 5 The netpage page server maintains a unique page instance for each printed netpage, allowing it to maintain a distinct set of user-supplied values for input fields in the page description for each printed netpage.

10 The relationship between the page description, the page instance, and the printed netpage is shown in Figure 3. The printed netpage may be part of a printed netpage document 45. The page instance is associated with both the netpage printer which printed it and, if known, the netpage user who requested it.

15 In a preferred form, each tag identifies the region in which it appears, and the location of that tag within the region. A tag may also contain flags which relate to the region as a whole or to the tag. One or more flag bits may, for example, signal a tag sensing device to provide feedback indicative of a function associated with the immediate area of the tag, without the sensing device having to refer to a description of the region. A netpage pen may, for example, illuminate an "active area" LED when in the zone of a hyperlink.

20 In a preferred embodiment, each tag contains an easily recognized invariant structure which aids initial detection, and which assists in minimizing the effect of any warp induced by the surface or by the sensing process. The tags preferably tile the entire page, and are sufficiently small and densely arranged that the pen can reliably image at least one tag even on a single click on the page. It is important that the pen recognize the page ID and position on every interaction with the page, since the interaction is stateless.

25 In a preferred embodiment, the region to which a tag refers coincides with an entire page, and the region ID encoded in the tag is therefore synonymous with the page ID of the page on which the tag appears. In other embodiments, the region to which a tag refers can be an arbitrary subregion of a page or other surface. For example, it can coincide with the zone of an interactive element, in which case the region ID can directly
30 identify the interactive element.

Each tag typically contains 16 bits of tag ID, at least 90 bits of region ID, and a number of flag bits. Assuming a maximum tag density of 64 per square inch, a 16-bit tag ID supports a region size of up to 1024 square inches. Larger regions can be mapped continuously without increasing the tag ID precision simply by using abutting regions and maps. The distinction between a region ID and a tag ID is mostly one of convenience. For most purposes the concatenation of the two can be considered as a globally unique tag ID. Conversely, it may also be convenient to introduce structure into the tag ID, for example to define the x and y coordinates of the tag. A 90-bit region ID allows 2^{90} ($\sim 10^{27}$ or a thousand trillion trillion) different regions to be uniquely identified. Tags may also contain type information, and a region may be tagged with a mixture of tag types. For example, a region may be tagged with one set of tags encoding x coordinates and another set, interleaved with the first, encoding y coordinates.

In one embodiment, 120 bits of tag data are redundantly encoded using a (15, 5) Reed-Solomon code. This yields 360 encoded bits consisting of 6 codewords of 15 4-bit symbols each. The (15, 5) code allows up to 5 symbol errors to be corrected per codeword, i.e. it is tolerant of a symbol error rate of up to 33% per codeword. Each 4-bit symbol is represented in a spatially coherent way in the tag, and the symbols of the six codewords are interleaved spatially within the tag. This ensures that a burst error (an error affecting multiple spatially adjacent bits) damages a minimum number of symbols overall and a minimum number of symbols in any one codeword, thus maximising the likelihood that the burst error can be fully corrected.

Any suitable error-correcting code can be used in place of a (15, 5) Reed-Solomon code, for example a Reed-Solomon code with more or less redundancy, with the same or different symbol and codeword sizes; another block code; or a different kind of code, such as a convolutional code (see, for example, Stephen B. Wicker, Error Control Systems for Digital Communication and Storage, Prentice-Hall 1995, the contents of which are herein incorporated by cross-reference).

~~One embodiment of the physical representation of the tag, shown in Figure 4a and described in our earlier application USSN 09/_____ (docket no. NPT002US), includes fixed target structures 15, 16, 17 and variable data areas 18. The fixed target structures allow a sensing device such as the netpage pen to detect the tag and infer its~~

~~three-dimensional orientation relative to the sensor. The data areas contain~~
representations of the individual bits of the encoded tag data. To maximise its size, each
data bit is represented by a radial wedge in the form of an area bounded by two radial
lines and two concentric circular arcs. Each wedge has a minimum dimension of 8 dots
5 at 1600 dpi and is designed so that its base (its inner arc), is at least equal to this
minimum dimension. The height of the wedge in the radial direction is always equal to
the minimum dimension. Each 4-bit data symbol is represented by an array of 2x2
wedges. The fifteen 4-bit data symbols of each of the six codewords are allocated to the
four concentric symbol rings 18a to 18d in interleaved fashion. Symbols are allocated
10 alternately in circular progression around the tag. The interleaving is designed to
~~maximise the average spatial distance between any two symbols of the same codeword.~~

In order to support "single-click" interaction with a tagged region via a sensing
device, the sensing device must be able to see at least one entire tag in its field of view
no matter where in the region or at what orientation it is positioned. The required
15 diameter of the field of view of the sensing device is therefore a function of the size and
spacing of the tags. Assuming a circular tag shape, the minimum diameter of the sensor
field of view 193 is obtained when the tags are tiled on a equilateral triangular grid, as
shown in Figure 4b.

The tag structure just described is designed to allow both regular tilings of
20 planar surfaces and irregular tilings of non-planar surfaces. Regular tilings are not, in
general, possible on non-planar surfaces. In the more usual case of planar surfaces where
regular tilings of tags are possible, i.e. surfaces such as sheets of paper and the like, more
efficient tag structures can be used which exploit the regular nature of the tiling.

An alternative tag structure more suited to a regular tiling is shown in Figure
25 5a. The tag 4 is square and has four perspective targets 17. It is similar in structure to
tags described by Bennett et al. in US Patent 5,051,746. The tag represents sixty 4-bit
Reed-Solomon symbols 47, for a total of 240 bits. The tag represents each one bit as a
dot 48, and each zero bit by the absence of the corresponding dot. The perspective targets
are designed to be shared between adjacent tags, as shown in Figures 5b and 5c. Figure
30 5b shows a square tiling of 16 tags and the corresponding minimum field of view 193,
which must span the diagonals of two tags. Figure 5c shows a square tiling of nine tags,

containing all one bits for illustration purposes.

Using a (15, 7) Reed-Solomon code, 112 bits of tag data are redundantly encoded to produce 240 encoded bits. The four codewords are interleaved spatially within the tag to maximize resilience to burst errors. Assuming a 16-bit tag ID as before, this allows a region ID of up to 92 bits. The data-bearing dots 48 of the tag are designed to not overlap their neighbors, so that groups of tags cannot produce structures which resemble targets. This also saves ink. The perspective targets therefore allow detection of the tag, so further targets are not required.

Although the tag may contain an orientation feature to allow disambiguation of the four possible orientations of the tag relative to the sensor, it is also possible to embed orientation data in the tag data. For example, the four codewords can be arranged so that each tag orientation contains one codeword placed at that orientation, as shown in Figure 5d, where each symbol is labelled with the number of its codeword (1-4) and the position of the symbol within the codeword (A-O). Tag decoding then consists of decoding one codeword at each orientation. Each codeword can either contain a single bit indicating whether it is the first codeword, or two bits indicating which codeword it is. The latter approach has the advantage that if, say, the data content of only one codeword is required, then at most two codewords need to be decoded to obtain the desired data. This may be the case if the region ID is not expected to change within a stroke and is thus only decoded at the start of a stroke. Within a stroke only the codeword containing the tag ID is then desired. Furthermore, since the rotation of the sensing device changes slowly and predictably within a stroke, only one codeword typically needs to be decoded per frame.

It is possible to dispense with perspective targets altogether and instead rely on the data representation being self-registering. In this case each bit value (or multi-bit value) is typically represented by an explicit glyph, i.e. no bit value is represented by the absence of a glyph. This ensures that the data grid is well-populated, and thus allows the grid to be reliably identified and its perspective distortion detected and subsequently corrected during data sampling. To allow tag boundaries to be detected, each tag data must contain a marker pattern, and these must be redundantly encoded to allow reliable detection. The overhead of such marker patterns is similar to the overhead of explicit

perspective targets. One such scheme uses dots positioned at various points relative to grid vertices to represent different glyphs and hence different multi-bit values (see Anoto Technology Description, Anoto April 2000).

Decoding a tag results in a region ID, a tag ID, and a tag-relative pen transform.

- 5 Before the tag ID and the tag-relative pen location can be translated into an absolute location within the tagged region, the location of the tag within the region must be known. This is given by a tag map, a function which maps each tag ID in a tagged region to a corresponding location. A tag map reflects the scheme used to tile the surface region with tags, and this can vary according to surface type. When multiple tagged regions
- 10 share the same tiling scheme and the same tag numbering scheme, they can also share the same tag map. The tag map for a region must be retrievable via the region ID. Thus, given a region ID, a tag ID and a pen transform, the tag map can be retrieved, the tag ID can be translated into an absolute tag location within the region, and the tag-relative pen location can be added to the tag location to yield an absolute pen location within the
- 15 region.

- The tag ID may have a structure which assists translation through the tag map. It may, for example, encoded cartesian coordinates or polar coordinates, depending on the surface type on which it appears. The tag ID structure is dictated by and known to the tag map, and tag IDs associated with different tag maps may therefore have different
- 20 structures.

Two distinct surface coding schemes are of interest, both of which use the tag structure described earlier in this section. The preferred coding scheme uses "location-indicating" tags as already discussed. An alternative coding scheme uses "object-indicating" (or "function-indicating") tags.

- 25 A location-indicating tag contains a tag ID which, when translated through the tag map associated with the tagged region, yields a unique tag location within the region. The tag-relative location of the pen is added to this tag location to yield the location of the pen within the region. This in turn is used to determine the location of the pen relative to a user interface element in the page description associated with the region.
- 30 Not only is the user interface element itself identified, but a location relative to the user interface element is identified. Location-indicating tags therefore trivially support the

capture of an absolute pen path in the zone of a particular user interface element.

sub 99 ~~An object-indicating (or function-indicating) tag contains a tag ID which~~
directly identifies a user interface element in the page description associated with the
region (or equivalently, a function). All the tags in the zone of the user interface element
5 identify the user interface element, making them all identical and therefore
indistinguishable. Object-indicating tags do not, therefore, support the capture of an
absolute pen path. They do, however, support the capture of a relative pen path. So long
as the position sampling frequency exceeds twice the encountered tag frequency, the
displacement from one sampled pen position to the next within a stroke can be
10 unambiguously determined. As an alternative, the netpage pen 101 can contain a pair or
motion-sensing accelerometers, as described in our earlier application USSN
09/ (docket no. NPS001US).

With either tagging scheme, the tags function in cooperation with associated
visual elements on the netpage as user interactive elements in that a user can interact
15 with the printed page using an appropriate sensing device in order for tag data to be read
by the sensing device and for an appropriate response to be generated in the netpage
system.

Each application user interface flow is illustrated as a collection of documents
linked by command arrows. A command arrow indicates that the target document is
20 printed as a result of the user pressing the corresponding command button on the source
page. Some command arrows are labelled with multiple commands separated by slashes
(/s), indicating that any one of the specified commands causes the target document to
be printed. Although multiple commands may label the same command arrow, they
typically have different side-effects.

25 In application terms, it is important to distinguish between netpage documents
and netpage forms. Documents contain printed information, as well as command buttons
which can be pressed by the user to request further information or some other action.
Forms, in addition to behaving like normal documents, also contain input fields which
can be filled in by the user. They provide the system with a data input mechanism. It is
30 also useful to distinguish between documents which contain generic information and
documents which contain information specific to a particular interaction between the

user and an application. Generic documents may be pre-printed publications such as magazines sold at news stands or advertising posters encountered in public places. Forms may also be pre-printed, including, for example, subscription forms encountered in pre-printed publications. They may, of course, also be generated on-the-fly by a netpage printer in response to user requests. User-specific documents and forms are normally generated on the fly by a netpage printer in response to user requests. Figure 6 shows a generic document 990, a generic form 991, a user-specific document 992, and a user-specific form 993.

Netpages which participate in a user interface flow are further described by abstract page layouts. A page layout may contain various kinds of elements, each of which has a unique style to differentiate it from the others. As shown in Figure 7, these include fixed information 994, variable information 995, input fields 996, command buttons 997, draggable commands 998, and text hyperlinks or hypertext links 999.

When a user interface flow is broken up into multiple diagrams, any document which is duplicated is shown with dashed outlines in all but the main diagram which defines it.

ROUTE PLANNING VIA INTERACTIVE PAPER

The netpage system provides a route planning application which allows a user to plan a route between two locations. The user can specify a point of origin and a destination by pressing on a netpage street map or by pressing the <Location> button on an advertisement or on someone's business card. The netpage route planning application can assume that the starting location is the location of the netpage printer through which the user is interacting, but allows the user to explicitly specify a different starting location, as well as to modify the default route and specify route constraints in the usual way supported by route-planning systems.

The same technique allows a location to be specified as the destination to any route planning system, for example an automobile navigation system's route planner. An automobile navigation system typically determines the location of the car via GPS, shows a local map to the driver on a color display, assists the driver in planning a route,

and gives the driver verbal instructions on following a route, cued to the changing location of the car. The user can press on a location on a netpage street map and then press the <destination> button on the navigation system. The navigation system automatically programs the map location as the destination. The user also can press the

5 <location> button on an advertisement or on someone's business card and then press the <destination> button on the navigation system. This yields a potentially more accurate location than one derived from a map. The present application is described in terms of an automobile navigation system, but applies equally to any portable navigation system.

ROUTE PLANNING OBJECT MODEL

10 The Route Planning object model revolves around maps and trip information.

A route planning provider 500 has a unique identifier 803 and name. A route planning provider 500 has a number of route planning users 501. Each route planning user 501 has an alias identifier 65 unique within the scope of the route planning provider. Each route planning user 501 represents a particular netpage user 800 to the provider. A

15 netpage user 800, on the other hand, can be a route planning user 501 of any number of providers 500. The Route Planning User class diagram is shown in Figure 8.

The netpage registration server 11 maintains a "clipboard" for each netpage user 800 and for each netpage printer 601. A clipboard provides a standard mechanism for one application to share data with another application, without the two applications needing to have any knowledge of each other.

20 ~~When a geographically-oriented netpage application determines that a user has selected a geographic location, it stores the selected location (or area) on the clipboard of both the user and the printer through which the user is interacting. This is then available for retrieval by other geographically-oriented applications, including the netpage route~~

25 ~~planning application. Further details of the clipboard are described in our co-filed application USSN 09/ (docket no. NPA053US).~~

A location may be a netpage map point clicked on by the user. Alternatively it may be the location of a person or business obtained by clicking on the <Location> button on an advertisement or business card.

30 A route planning provider 500 can have a number of detailed maps 502, each

with a unique identifier, a description, a scale, the latitude and longitude of the top left corner of the map, a horizontal and vertical size, and a map image or other geographical map description. Each map has a number of map features 503. Each map feature 503 has a latitude and longitude, a name and a type. The Map class diagram is shown in Figure 9.

5 A route planning provider 500 has a database of streets 505, each with a name. Each street 505 may comprise many street segments 506. A street segment 506 is part of a street running between two intersections 507. Each street segment 506 has a one-way flag, to indicate if the street segment is one-way or two-way, and a type. The street type may be a highway, tollway, suburban street, lane etc. There may be a relationship
10 between two street segments indicating that turning from one street segment to another is not allowed. A street segment has a start intersection and an end intersection. Each intersection 507 has a location specified as a latitude and longitude. The Street class diagram is shown in Figure 10.

 A user 501 can plan a number of trips with a route planning provider. The trip
15 information 508 comprises a trip number, the date and time the trip information was entered, the origin and destination of the trip, and trip preferences. The trip preferences comprise a number of “avoid” features 509 and a number of “favor” features 510, which are taken into account when planning the suggested trip route. The Route Planning class diagram is shown in Figure 11. The route features 511 include scenic roads 512,
20 mountain roads 513, seasonal roads 514, interstate roads 515 and tollways 516. The route planning provider can support other route features as well. The Route Feature class diagram is shown in Figure 12.

 Each set of trip information 508 has a suggested route 517 determined by the route planning application. The suggested route 517 is made up of a number of route
25 segments 518. Each route segment 518 has a segment number, start point, end point, road number, distance (between the start and end points of the route segment), travel time, and a description. A route segment 518 is made up of one or more street segments 506. The Route Plan class diagram is shown in Figure 13.

ROUTE PLANNING USER INTERFACE

The user may obtain the Route Planner Origin page 520 from a variety of links including:

- the netpage printer's help menu 46
- 5 • the netpage user's own bookmark

The Route Planning user interface flow is shown in Figure 14.

Trip Origin

Sub A10
10 ~~The Trip Origin page 520 is shown in Figure 15. The user can specify a point of origin for the trip in one of several ways. The user can click on a point on a netpage map and then click the <Last Selected Location> button 526 on the Trip Origin page 520. Printing maps and selecting geographic locations via printed netpage maps is described in more detail in our co-filed application USSN 09/_____ (docket no. NPA053US). The user also can press the <Location> button on an advertisement or on someone's business card and then press the <Last Selected Location> button 526. This~~
15 ~~yields a potentially more accurate location than one derived from a map.~~

The last user-selected location is retrieved from the user's clipboard on the registration server, using the user's alias identifier 65.

If the user's point of origin is their current location, determined by the location of the printer through which the user is interacting, the user can click the <Current
20 Location> button 527.

Alternatively the user can specify another point of origin by writing the place name or address in the <origin> field, and clicking the <Other Location> button 528. If the specified origin is ambiguous, such as a place name for which there are matches in several states, a Clarify Origin page 521 is printed, giving a list of more detailed place
25 names for the user to select from.

The user can click <Reset Form> to print a blank Trip Origin page 520.

When the trip origin is chosen the Trip Destination page 522 is printed, as shown in Figure 16.

Trip Destination

The user can specify a trip destination by clicking on a point on a netpage map and then clicking the <Last Selected Location> button on the Trip Destination page 522 (Figure 16). The user also can press the <Location> button on an advertisement or on
5 someone's business card and then press the <Last Selected Location>. This yields a potentially more accurate location than one derived from a map.

The last user-selected location is retrieved from the user's clipboard on the registration server 11, using the user's alias identifier 65.

Alternatively the user can specify another destination by writing the place name
10 or address in the <destination> field, and clicking the <Other Location> button. If the specified destination is ambiguous, such as a place name for which there are matches in several states, a Clarify Destination page 523 is printed, giving a list of more detailed place names for the user to select from.

The user can click <Reset Form> to print a blank Trip Destination page 522.

15 When the trip destination is chosen the Preferences page 524 is printed, as shown in Figure 17.

Trip Preferences

The user can specify trip preferences on the Preferences page 524 (Figure 17). This page gives a list of route features including tollways, mountain roads, scenic roads,
20 seasonal roads, and interstate roads. The user can specify a particular interstate road number. Optionally the route planning provider may include more route features.

The user can chose to favor or avoid each route feature by marking the appropriate checkbox. The user indicates no preference for a particular route feature by not marking either checkbox.

25 If no preferences are indicated, i.e. all the checkboxes are left blank, the quickest route is suggested.

Optionally the provider can allow the user to specify "detour data" (roads to exclude from the route plan) and other route constraints or preferences.

The user can click <Reset Form> to print a blank Preferences page 524.

When the desired preferences are indicated the user clicks the <Plan Route> button 529. The Route Plan page 525 is printed, as shown in Figure 18.

Route Plan

5 The Route Plan page 525 (Figure 18) lists the trip information given by the user, and shows a suggested route plan for the trip. The page lists the trip origin, trip destination, trip distance (calculated from the route segment distances), the trip travel time (calculated from the route segment travel times), the route preferences, and the route plan (i.e. directions).

10 The route plan is the route segment information as determined by the route planning application. Optionally, the provider may include extra functionality or information with the route plan. For example the route plan may also include services, attractions etc. which may be encountered en-route.

Optionally the route plan can include advertising.

Automobile Navigation System Route Planner

15 A route planning system may be located within an automobile or personal navigation system. Alternatively the route planning system may be located on the netpage system, accessed via the netpage network.

20 The netpage system provides a convenient way for a driver to specify a location to a route planning system. The user can press on a location on a netpage street map, or press the <location> button on an advertisement or on someone's business card.

The user-selected location is stored as a map location list object on the user's clipboard and on the current printer's clipboard, on a netpage registration server. This can be accessed by the route planning system.

Navigation System with Netpage Network Connectivity

25 An automobile navigation system optionally contains a netpage printer, allowing the navigation system to obtain information from the netpage system via the netpage printer. In addition to providing connectivity to a netpage pen and to the netpage network, this allows the user to print more detailed maps, or other information regarding local businesses etc.

The driver specifies a destination to the automobile navigation system's route planner by pressing on a location on a netpage street map and then pressing the <destination> button on the navigation system. The navigation system automatically programs the map location as the destination. The user also can press the <location> button on an advertisement or on someone's business card and then press the <destination> button on the navigation system. This yields a potentially more accurate location than one derived from a map.

When the user presses on a location, the click is sent to the netpage printer, and then to the netpage page server in the usual way. The selected location is stored as a map location list object on the user's clipboard and on the printer's clipboard, on a netpage registration server.

When the user presses the <Destination> button on the navigation system the navigation system retrieves the location from the map location list object on the printer's clipboard, via the attached netpage printer. The navigation system doesn't know who the user is and therefore cannot look up the user's clipboard.

Communication between the navigation system 530 and the netpage printer 601 is via the printer's high-speed serial interface, as shown in Figure 19.

Alternatively the navigation system 530 can contain a netpage pen interface (i.e. RF transceiver) and a netpage network interface 751 (but no netpage print engine). The navigation system itself then acts as a netpage device, mediating netpage pen interaction with the netpage system etc. and having its own "printer" ID. In this scenario the user cannot obtain printed netpage output.

Navigation System Without Netpage Network Connectivity

Another alternative configuration is for the automobile navigation system to contain a netpage pen interface, but no netpage network interface 751. The route planning system is embedded in the navigation system, and the location information is stored locally (or on some removable medium such as CD-ROM). The required location information relating to a map click can be retrieved from the route planning system database.

The latitude and longitude of a map position can be encoded directly in each

netpage tag 4. There is sufficient precision in a netpage tag 4 to represent a global location to an accuracy of better than 1 meter. The tag can include information about the scale of the map so that the system can infer a more accurate location from the position of the pen relative to the tag. Each tag can also be indicative of a page position in the usual way, with the system translating a pen position to a map location via map information stored on the system.

Navigation System Without a Route Planner

Some navigation systems do not provide automatic route generation, but instead allow the user to select and record a route. This route information is stored on the navigation system and used to provide directions to the user. In this case, a route plan can be generated by the forms-based netpage route planning system, and then the route information downloaded to the navigation system.

Alternatively, the user can program an explicit route manually by specifying the start and end point, and each intermediate point to the navigation system using the navigation system's user interface.

Route Planning Method

The route plan can be determined in a number of ways. There are a variety of algorithms available.

When the route planning application plans the route, it views the database of street segments and intersections as a graph, where each intersection is a vertex of the graph and each street segment is an edge. It assigns each edge a weight, representing the road distance. Weights can also be set to take into consideration the user's specified route preferences.

It computes the shortest path between two vertices in the graph using a single-source shortest-path algorithm.

The route planning application can alternatively use travelling time as the edge weight in order to find the fastest route between two points. In this case, highways have a smaller weight than suburban streets, for example.

CONCLUSION

The present invention has been described with reference to a preferred embodiment and number of specific alternative embodiments. However, it will be appreciated by those skilled in the relevant fields that a number of other embodiments, 5 differing from those specifically described, will also fall within the spirit and scope of the present invention. Accordingly, it will be understood that the invention is not intended to be limited to the specific embodiments described in the present specification, including documents incorporated by cross-reference as appropriate. The scope of the invention is only limited by the attached claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000